

# Loads

## High performance anchor FH II

Permissible loads of a single anchor<sup>1)</sup> in normal concrete of strength class C20/25.

For the design the complete current assessment ETA-07/0025 has to be considered.

Type	Material/ surface <sup>2)</sup>					Cracked concrete				Non-cracked concrete				
		Effective anchorage depth $h_{ef}$ [mm]	Minimum member thickness $h_{min}$ [mm]	Instal- lation torque $T_{inst}$ [Nm]		Permissible tension ( $N_{perm}$ ) and shear loads ( $V_{perm}$ ); minimum spacing ( $s_{min}$ ) and edge distances ( $c_{min}$ ) with reduced loads	$N_{perm}$ <sup>3)</sup> [kN]	$V_{perm}$ <sup>3)</sup> [kN]	$s_{min}$ <sup>3)</sup> [mm]	$c_{min}$ <sup>3)</sup> [mm]	$N_{perm}$ <sup>3)</sup> [kN]	$V_{perm}$ <sup>3)</sup> [kN]	$s_{min}$ <sup>3)</sup> [mm]	$c_{min}$ <sup>3)</sup> [mm]
FH II 10 S	gvz	40	80	10	3.6	4.1	40	40	5.9	5.9	40	40		
	R	40	80	15	3.6	4.1	40	40	5.9	5.9	40	40		
FH II 12 S	gvz	60	120	22.5	5.7	15.2	50	50	10.9	18.9	60	60		
	R	60	120	25	5.7	15.2	50	50	9.5	17.7	60	60		
FH II 15 S	gvz	70	140	40	7.6	19.2	60	60	13.7	27.4	70	70		
	R	70	140	40	7.6	19.2	60	60	13.7	27.4	70	70		
FH II 18 S	gvz	80	160	80	11.7	23.5	70	70	16.8	33.5	80	80		
	R	80	160	100	11.7	23.5	70	70	16.8	33.5	80	80		
FH II 24 S	gvz	100	200	160	16.4	32.8	80	80	23.4	46.9	100	100		
	R	100	200	160	16.4	32.8	80	80	23.4	46.9	100	100		
FH II 28 S	gvz	125	250	180	22.9	45.8	100	100	32.8	65.9	120	120		
FH II 32 S	gvz	150	300	200	30.1	60.2	120	120	43.0	86.1	160	180		
FH II 10 SK	gvz	40	80	10	3.6	4.1	40	40	5.9	5.9	40	40		
FH II 12 SK	gvz	60	120	22.5	5.7	15.2	50	50	10.9	18.9	60	60		
	R	60	120	25	5.7	15.2	50	50	10.9	18.9	60	60		
FH II 15 SK	gvz	70	140	40	7.6	19.2	60	60	13.7	27.4	70	70		
	R	70	140	40	7.6	19.2	60	60	13.7	27.4	70	70		
FH II 18 SK	gvz	80	160	80	11.7	23.5	70	70	16.8	33.5	80	80		
	R	80	160	100	11.7	23.5	70	70	16.8	33.5	80	80		
FH II 10 H	gvz	40	80	10	3.6	4.1	40	40	5.9	5.9	40	40		
FH II 12 H	gvz	60	120	22.5	5.7	15.2	50	50	10.9	15.5	60	60		
FH II 15 H	gvz	70	140	40	7.6	19.2	60	60	13.7	24.5	70	70		
FH II 18 H	gvz	80	160	80	11.7	23.5	70	70	16.8	33.5	80	80		
FH II 10 B	gvz	40	80	10	3.6	4.1	40	40	5.9	5.9	40	40		
FH II 12 B	gvz	60	120	17.5	5.7	15.2	50	50	10.9	15.5	60	60		
FH II 15 B	gvz	70	140	38	7.6	19.2	60	60	13.7	24.5	70	70		
FH II 18 B	gvz	80	160	80	11.7	23.5	70	70	16.8	33.5	80	80		
FH II 24 B	gvz	100	200	120	16.4	32.8	80	80	23.4	46.9	100	100		
FH II 28 B	gvz	125	250	180	22.9	45.8	100	100	32.7	65.5	120	120		
FH II 32 B	gvz	150	300	200	30.1	60.2	120	120	43.0	86.1	160	180		

<sup>1)</sup> Design according to EN 1992-4:2018 (for static resp. quasi-static loads). The partial safety factors for material resistance as regulated in the ETA as well as a partial safety factor for load actions of  $\gamma_L = 1.4$  are considered. As a single anchor counts e.g. an anchor with a spacing  $s \geq 3 \times h_{ef}$  and an edge distance  $c \geq 1.5 \times h_{ef}$ . Accurate data see ETA.

<sup>2)</sup> Further steel grades, versions and technical data see ETA, e.g. for dry internal conditions, galvanised steel (gvz); for damp interiors and for outdoor use, stainless steel (R).

<sup>3)</sup> In the case of combinations of tension and shear loads, bending moments with reduced or minimum spacing and edge distances (anchor groups), the design must be carried out in accordance with the provisions of the complete ETA and the provisions of the EN 1992-4:2018. We recommend using our anchor design software C-FIX.